

400A TPN GLASGOW Switch-disconnector (surface-mounted), RAL 7004

Part no. 403GN 304096

| neral specifications | |
|---|--|
| Product name | Eaton Industrial Switch & Fuse Gear Exel/Glasgow LV systems Switch- & Controlgear Enclosure |
| Part no. | 403GN |
| EAN | 9010238196186 |
| Product Length/Depth | 322 millimetre |
| Product height | 521 millimetre |
| Product width | 487 millimetre |
| Product weight | 34.07 kilogram |
| Compliances | RoHS conform |
| Product Tradename | Industrial Switch & Fuse Gear Exel/Glasgow |
| Product Type | LV systems |
| Product Sub Type | Switch- & Controlgear Enclosure |
| Countries | South Africa Central African Republic United Kingdom of Great Britain and Northern Ireland United Arab Emirates |
| roduct Specification Details | |
| Construction size (fuse inserts) | Cylindrical |
| Degree of protection | IP40 Other |
| Housing depth | 322 mm |
| Housing height | 521 mm |
| Housing of equipment fuse switch disconnector | Other |
| Housing width | 487 mm |
| Number of poles | Four-pole |
| Rated insulation voltage (Ui) | 660 V |
| Rated operating voltage (Ue) at AC - max | 415 V |
| Rated operational current | 400 A |

Technical data ETIM 9.0

Low-voltage industrial components (EG000017) / Fuse switch disconnector with housing (EC000249)

Electric engineering, automation, process control engineering / Low-voltage switch technology / Off-load switch, circuit breaker, control switch / Safety circuit breaker housing (ecl@ss13-27-37-14-13 [AKF070018])

| (ECI@5513-27-37-14-13 [AKI 070010]) | | |
|-------------------------------------|----|-------------|
| Number of poles | | 4 |
| Rated operation current le | Α | 400 |
| Max. rated operation voltage Ue AC | V | 415 |
| Rated insulation voltage Ui | V | 660 |
| Construction size fuse inserts | | Cylindrical |
| With error protection | | No |
| Housing width | mm | 487 |
| Housing depth | mm | 322 |
| Height of housing | mm | 521 |
| Degree of protection (IP) | | Other |
| Degree of protection (NEMA) | | Other |