

Firestay 5/7W LED CCT Dimmable Wattage Switchable Centre Tilt Downlight

Part Code: 08190V2

Our flagship downlight has received a major facelift for 2024! The Firestay CCT now includes a 4-way colour switch and 2-way wattage switch as standard. With an upgraded 10-year warranty, the new Firestay CCT is truly a fit and forget market leading downlight.

- Firestay Certification: 30, 60 and 90 minute solid joist ceilings, 30 minute I-Joist & Metal Web ceiling systems
- IP65
- Front CCT/Wattage Switch
- Mains Dimmable as standard
- Spacer plate options available



Changeable
Bezels



**Colour
Temperature**
Options



IP65
Rating



Wattage
Switchable



FirestayLED

CCT 3 way selectable colour switch



Product Category Fittings / Downlights

Application LED Downlight

Product Warranty 10 Years

EAN 5013588900162

Commodity Code 9405423990

Country of Origin CN

Technical Specification

Watts (W)	5/7
Volts (V)	220/240
Colour Temp (K)	2700/3000/4000/6000
Lumens (lm)	620-880
Lumens per Watt (lm/W)	89-126
Candelas (cd)	524-740
CRI (ra)	85
Frequency (Hz)	50/60
LED Drive Current	18mA
Energy Consumption (kWh/1000h)	7
Life Hours	70000
Switching Cycles	100000
Energy Rating	E
Impact Protection	IK7
IP Rating	IP65

Packaging Information

Height (mm)	68
Width (mm)	105
Diameter (mm)	105
Downlight Cut Out (mm)	80
Individual Product Weight (kg)	0.41
Single Carton Height (mm)	110
Single Carton Width (mm)	110
Single Carton Depth (mm)	115
Single Carton Weight (kg)	0.54
Individual Volume	0.0013915
Inner Box Qty	10
Inner Carton Barcode	08190V2000010
Inner Box Height (mm)	565
Inner Box Width (mm)	230
Inner Box Depth (mm)	125
Inner Box Weight (kg)	4.75
Inner Box Volume	0.01624375
Outer Box Qty	20
Outer Carton Barcode	08190V2000020
Outer Box Height (mm)	590
Outer Box Width (mm)	255
Outer Box Depth (mm)	280
Outer Box Weight (kg)	9.5
Outer Box Volume	0.042126
Plastic Packaging Weight (kg)	0.048

FirestayLED

CCT 3 way selectable colour switch

Additional Information

Beam Angle

60°