



Firestay 5/7W LED CCT Dimmable Wattage Switchable Downlight with Tool **Free Termination**

Part Code: 10510v2

Our flagship downlight has received a major facelift. The Firestay CCT now includes a 4-way colour switch and 2-way wattage switch as standard. With an upgraded 10-year warranty, the new Firestay CCT is truly a fit and forget market leading downlight.

- Firestay Certification: 30, 60 and 90 minute solid joist ceilings, 30 minute I-Joist & Metal Web ceiling systems
- IP65
- Front CCT/Wattage Switch
- · Mains Dimmable as standard
- Compatible with most branded Trailing Edge Dimmers, including the BELL Smart Universal LED Trailing/Leading Edge Dimmer Module Code: 10803















Email: technical@belllighting.co.uk Telephone: 01924 893380

www.belllighting.co.uk








Product Category	Fittings / Downlights
Application	LED Downlight
Product Warranty	10 Years
EAN	5013588900018
Commodity Code	9405423990
Country of Origin	CN

Technical Specification		
Watts (W)	5/7	
Volts (V)	220/240	
Colour Temp (K)	2700/3000/4000/6000	
Lumens (lm)	5W = 684 (2700K) / 712 (3000K) / 793 (4000K) / 746 (6000K) - 7W = 1048 (2700K) / 1115 (3000K) / 1010 (4000K) / 970 (6000K)	
Lumens per Watt (lm/W)	137-159	
Candelas (cd)	550-720	
CRI (ra)	85	
Frequency (Hz)	50/60	
Life Hours	70000	
Switching Cycles	100000	
Impact Protection	IK07	
IP Rating	IP65	

Packaging Information		
Height (mm)	45	
Diameter (mm)	82	
Downlight Cut Out (mm)	68	
Individual Product Weight (kg)	0.215	
Single Carton Height (mm)	100	
Single Carton Width (mm)	88	
Single Carton Depth (mm)	85	
Single Carton Weight (kg)	0.3	
Individual Volume	0.00075	
Inner Box Qty	10	
Inner Carton Barcode	10510V2000010	
Inner Box Height (mm)	455	
Inner Box Width (mm)	210	
Inner Box Depth (mm)	95	
Inner Box Weight (kg)	3.18	
Inner Box Volume	0.00908	
Outer Box Qty	20	
Outer Carton Barcode	10510V2000020	
Outer Box Height (mm)	465	
Outer Box Width (mm)	220	
Outer Box Depth (mm)	205	
Outer Box Weight (kg)	6.42	
Outer Box Volume	0.02097	
Plastic Packaging Weight (kg)	0.035	
UNSPSC Code	39111515	
Minimum Order Quantity	1	



Email: technical@belllighting.co.uk **Telephone:** 01924 893380





Additional Information		
Beam Angle	60°	

Email: technical@belllighting.co.uk **Telephone:** 01924 893380